

CCREFRACTORIES TECHNICAL DATA SHEET

MAGNESIA-CHROME BRICK (MC-70)

RELIABLE HIGH-TEMPERATURE PERFORMANCE WITH BALANCED SLAG RESISTANCE

The Magnesia-Chrome Brick MC-70 is formulated with high-purity fused magnesia and chromite, providing an optimal balance between thermal shock resistance, slag corrosion resistance, and mechanical strength. This product is widely used in non-ferrous metallurgy, particularly in zones requiring enhanced durability in oxidising and mildly reducing atmospheres.

TECHNICAL SPECIFICATIONS	
PROPERTY	MC-70
MgO (%)	≥70
Cr ₂ O ₃ (%)	≥ 14 – 18
Apparent Porosity (%)	≤18
Bulk Density (g/cm³)	≥ 3.05
Cold Crushing Strength (MPa)	≥ 90
Modulus of Rupture at 1400°C (MPa)	≥10
Refractoriness Under Load (0.2 MPa, °C)	≥ 1650
Thermal Conductivity at 1000°C (W/m·K)	2.2 – 2.5
Maximum Service Temperature (°C)	1750
Bond Type	Fused Magnesia / Direct-Bonded Chrome

PACKAGING & SUPPLY

- Delivered in export-ready packaging on heat-treated pallets
- Optional corner- and key-brick formats available
- Full quality traceability and technical compliance documentation provided

INSTALLATION NOTES

- Use with compatible chrome-based mortars for optimal joint sealing
- Proper drying and controlled preheating procedures are recommended
- Inspect for tight brick alignment in tapping and high-erosion zones

ENVIRONMENTAL & SAFETY NOTES

- Manufactured under controlled Cr(VI) levels to meet health and safety standards
- Promotes extended refractory service life, minimising waste generation
- · Full MSDS and handling guidelines available upon request

KEY APPLICATIONS

- Flash Smelting Furnaces (Walls & Roofs)
- · Slag Cleaning Furnaces
- Rotary Kilns for Copper/Nickel Production
- · Secondary Smelting Chambers
- Tapping Channels and Slag Runners

PERFORMANCE CHARACTERISTICS

- Stable structural integrity under cyclic thermal load
- High corrosion resistance to both basic and amphoteric slags
- Maintains dimensional accuracy over prolonged campaigns
- Adaptable for both vertical and horizontal furnace configurations



