

CREFRACTORIES TECHNICAL DATA SHEET

HIGH ALUMINA BRICK (HA-80)

VERSATILE REFRACTORY FOR HIGH-TEMPERATURE INDUSTRIAL APPLICATIONS

The High Alumina Brick HA-80 is manufactured using carefully selected bauxite raw materials and sintered at high temperatures to ensure excellent thermal stability, mechanical strength, and slag resistance. With 80% Al₂O₃ content, this product is engineered for use across a broad range of high-temperature industrial applications, particularly where resistance to chemical attack and structural load are critical.

TECHNICAL SPECIFICATIONS	
PROPERTY	HA-80
Al ₂ O ₃ (%)	≥ 80
Fe ₂ O ₃ (%)	≤2.5
Apparent Porosity (%)	≤ 22
Bulk Density (g/cm³)	≥ 2.7
Cold Crushing Strength (MPa)	≥ 80
Modulus of Rupture at 1400°C (MPa)	≥9
Refractoriness Under Load (0.2 MPa, °C)	≥ 1550
Thermal Conductivity at 1000°C (W/m·K)	1.5 – 2.1
Maximum Service Temperature (°C)	1700
Bond Type	Sintered Alumin a

Packed on heat-treated export pallets with shrink-wrap protection Available in standard arch, wedge, and rectangular shapes Full QA documentation and batch traceability provided Lay using alumina-rich mortar for maximum adhesion Ensure proper bedding and joint alignment to prevent uneven stress Ideal for both cold and hot repair interventions

ENVIRONMENTAL & SAFETY NOTES

- Manufactured in ISO 9001 and ISO 14001 certified facilities
- Contains no asbestos or hazardous additives
- · Long service life contributes to reduced waste and energy savings

KEY APPLICATIONS

- · Cement Preheaters & Coolers
- · Iron & Steel Reheating Furnaces
- Incinerators and Boiler Linings
- · Ceramic and Glass Furnace Walls
- · Lime Shaft Kilns and Soaking Pits

PERFORMANCE CHARACTERISTICS

- High resistance to slag attack, spalling, and abrasion
- Stable performance across cyclical heating conditions
- Well-suited for both oxidising and reducing atmospheres
- Maintains compressive strength and dimensional stability at elevated temperatures



